

CAM 4CH+2 POE SWITCH

4+2 port POE switch

Manufacturer: [AMIKO](#)

Description

- 4x 10/100M Ethernet ports with PoE support
- 2x 10/100M Ethernet ports
- IEEE802.3af PoE protocol support
- Maximum 15.4W power output per interface
- 60W maximum combined power output
- Automatic detection of Powered Devices
- Flow control for Full Duplex operation

Network Connections:

Port 1-4: 10/100M with PoE

Port 5-6 (WAN): 10/100M

Transmission distance: ~100m (max.)

Transmission medium: CAT5/5e/6 standard network cable

Network Switch:

Network Standards: IEEE802.3/10 BASE-T Ethernet

IEEE802.3/100 BASE-TX Ethernet

IEEE802.3x Flow Control

Maximum Frame Size: 1528 Bytes

MAC address list: 2K

PoE standard: IEEE802.3af & IEEE802.3at

Power over Ethernet:

PoE Power Supply Type: End-span (1/2+, 3/6-)

Power Supply:

Power Adapter Voltage: Input: 180-240V AC at 50/60Hz

Output: DC 48V

Power Consumption: 75W

Physical Specifications:

Dimensions (WxDxH): 156mm x 139,6 mm x 29,6 mm

Working Temperature: 0°C ~ 40°C (5%-95%)

Storage Temperature: 20°C ~ 70°C

Weight: 780g