

CAM D20M530MF POE



5MP Outdoor Varifocal Dome IP POE

Manufacturer: [AMIKO](#)

Description

Camera

- Image Sensor: 1/2.8" SONY Starvis Back-illuminated CMOS sensor
- Resolution: 5MP
- Effective Pixels: 2616 (H) x 1964 (V)
- Compression: H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
- TV System: PAL/NTSC
- Electronic Shutter Time Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
- Minimum Illumination: 0.01Lux
- S/N Ratio: 52dB
- Scanning System: Progressive
- Video Output: Network

Lens

- Focus Length: 2.8-12mm
- Focus Control: Manual
- Lens Type: Varifocal
- Pixels: 5MP

Night Vision

- Infrared LED: 14μ x 24 pcs
- Infrared Distance: 20M

- IR Status:Auto Control
- IR Power: On
- Auto Control

Network

- Ethernet: RJ-45 (10/100Base-T)
- Wireless/Protocol: TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS, RTP,RTSP,RTCP,NTP,SMTP
- ONVIFSupport: ONVIF 2.4
- P2P: YES,
- Support QR Code
- POE: Optional/Internal, Support
- IEEE 802.3at
- Video Delay: 0.3S (Within the Lan)
- Main Stream 2592*1944@20fp>
- Main Stream 2592*1536@25fps>
- Main Stream 2560*1440@25fps>
- Main Stream 1920*1080@25fps>
- Main Stream 1280*720@25fps>
- Sub Stream 720*480@25fps>
- Sub Stream 352*288@25fps>
- Tri Stream 352*288@15fps>
- Tri Stream 352*288@30fps>
- IE Brower: IE8-11, Google Chrome (lower than Ver44),
- Firefox (lower than Ver53), Mac Safari
- Smart Phone: iPhone, iPad, Android, Android Pad

Camera Features

- Color/ B&W (IR-CUT)

Interface

- SD Card Slot: Internal, Max 512GB

General

- Housing:Metal ,IP66
- Anti-cut BracketOptional
- IR Cut Filter
- Operation Temperature: -20? ~ +60? RH95% Max
- Storage Temperature: -20? ~ +60? RH95% Max
- Power Source: DC12V±10%, 950mA
- Dimension: ?119x 98(H)mm
- Weight: 800g