

## HD TAB 7 EVO



HD\_TAB\_7\_STC\_52f0daeb78650.jpg

COMBINED HD PROFESSIONAL ANALYZER, 4-2.250 MHz, for SAT QPSK/8PSK - TV COFDM & CATV QAM signals, with MPEG-2/4 H264 decoder and Analog Pictures TV & Radio

Manufacturer: [Rover](#)

### Description

- TV and CATV TUNER, extended band, 4-1000 MHz
- SAT TUNER, extended band, 930-2.250 MHz
- GSM extended band, 860-1.000 MHz for telephone repeater installation
- Exclusive patented ROVER AUTODISCOVERY system: auto-matically detects and selects analog and digital COFDM/QAM TV signals in both measurement and spectrum mode
- Spectrum in real time, fast and super fast with memory peak
- Detects, measures and SHOWS pictures of MPEG 2 and 4 H264 HD High Definition programs
- All the measurements, program lists, A/V PIDs, NET ID, LCN, settings and pictures on one screen
- Automatic quality analysis: FAIL-MARG-PASS
- Automemory, Manual memory & Datalogger functions
- HELP function automatically identifies all the signals with digital modulation SAT, TV and CATV
- USB storage memory stick
- OPTICAL POWER METER opt. with interchangeable FCST- SC connector for fiber optic testing (FTTH & FTTX) and troubleshooting
- MER versus CARRIER, MER measurement for DVB-T & T2 carriers opt.
- Barscan TV & CATV function from 10 to 100 channels on one screen
- TV & IF SAT test ICT FENITEL Spain
- Audio, AAC supplied, DOLBY opt.

- 7" TFT TOUCH display, 16:9, high resolution
- Weighs only 1.6 kg, dim: H 14 x L 24 x D 4 cm
- LI-ION-POLIMER 4A battery with 4 hour battery capacity
- Battery test function, to regenerate and measure the batteries and calibrate the battery indicator
- Supplied with transport padded bag, accessories, mains and vehicle battery chargers
- Free basic SW upgradeable on-line
- Remote monitoring
- Reflectometric measurements (opt.)

[Download Leaflet](#)