

TAP DER415



1st IF SAT tap-off, 4 outputs. Tap loss -15dB

Manufacturer: [Fagor](#)

Description

MODEL		TAP-OFFS									
Reference		DER 410	DER 415	DER 420	DER 425	DER 416	DER 426	DER 435	DER 418	DER 428	DER 438
Nr. of outputs		86274	86275	86276	86277	86278	86279	86280	86281	86282	86283
Covered band		4				6				8	
Tap Loss (a 0.5 dB)	5 - 2300 MHz	dB									
Through loss	5 - 47 MHz	10	15	20	25	15	20	25	15	20	25
	47 - 862 MHz	4	2	1	1	3,5	1,5	0,5	3,5	1,5	1
	960 - 2150 MHz	5	4	2	2	3	4,5	3,5	3	3,5	2
	2150 - 2300 MHz	5	4,5	3	3	5,5	3,5	2,5	5,5	3,5	2,5
Directional isolation	5 - 47 MHz	25	30	35	40	25	30	30	25	30	30
	47 - 862 MHz	27	28	30	30	25	30	30	25	25	25
	960 - 2150 MHz	25	25	25	25	22	25	25	22	25	25
	2150 - 2300 MHz	25	25	25	25	21	24	24	24	24	24
Output isolation	5 - 47 MHz	25	25	25	25	22	25	25	22	27	27
	47 - 862 MHz	25	25	25	25	22	25	25	22	27	27
	960 - 2150 MHz	21	22	22	22	22	22	20	22	22	22
	2150 - 2300 MHz	21	21	21	21	16	16	16	18	18	18
Return losses	5 - 862 MHz	dB									
	960 - 2150 MHz	10									
Min. screening factor	5 - 862 MHz	dB									
	960 - 2150 MHz	35									
Packing dimensions (10 u.)	mm	180 x 105 x 65					205 x 125 x 67				
Weight (10 u.)	Kg	0,70					1,10				