

TAP DER215



1st IF SAT tap-off, 2 outputs. Tap loss - 15dB

Manufacturer: [Fagor](#)

Description

MODEL		SPLITTERS					TAP-OFFS								
Reference		REP 304	REP 307	REP 400	REP 610	REP 616	DER 110	DER 116	DER 120	DER 126	DER 210	DER 216	DER 220	DER 226	
Nr. of outputs		85281	85282	85283	85284	85285	85286	85287	85288	85289	85270	85271	85272	85273	
Covered band	MHz						5 + 2300								
Tap Loss (a 0.5 dB)		5 - 2300 MHz	dB	—	—	—	—	10	15	20	25	10	15	20	25
Through loss	5 - 47 MHz	dB	4	6,5	7,5	10,5	11	3	1,5	1,1	1	3,5	2,5	1,5	1
	47 - 862 MHz	dB	4	7,5	8	11	12	1,8	1,5	1,1	1	3	2,2	1,5	1
	860 - 2150 MHz	dB	5,5	9	9,5	14,5	15,5	2,2	2,2	1,9	1,8	3,5	3	2,5	1,7
	2150 - 2300 MHz	dB	8	10	10,5	15	16	2,2	2,2	2,2	2,1	4	3	3	2,1
Directional isolation	5 - 47 MHz	dB	—	—	—	—	25	25	27	30	20	25	30	35	35
	47 - 862 MHz	dB	—	—	—	—	24	24	25	27	20	22	25	25	25
	860 - 2150 MHz	dB	—	—	—	—	23	23	23	24	15	22	22	25	25
	2150 - 2300 MHz	dB	—	—	—	—	23	23	23	24	15	22	22	25	25
Output isolation	5 - 47 MHz	dB	20	20	21	22	24	—	—	—	40	45	60	60	60
	47 - 862 MHz	dB	21	21	21	22	22	—	—	—	30	35	45	45	45
	860 - 2150 MHz	dB	20	21	21	21	21	—	—	—	25	30	35	35	35
	2150 - 2300 MHz	dB	20	20	21	20	21	—	—	—	25	30	35	35	35
Return losses	5 - 862 MHz	dB	12												
Min. screening factor	900 - 2150 MHz	dB	65												
Packing dimensions (10 u.)	mm	kg/1000	160 x 105 x 57			205 x 125 x 57			115 x 105 x 57			160 x 105 x 57			
Weight (10 u.)	Kg	0,50	0,60			1,10			0,50			0,60			